

Bottom Discharge Valve

Valve for fluid production through and around the pump

APPLICATIONS

- Bottom-anchor insert pumps
- Wells with corrosive fluid
- Wells with low to moderate amounts of sand

BENEFITS

- Prevents corrosive, stagnant fluid from attacking outside of pump
- Prevents solid material from settling on pump hold-down
- Enables maintaining full fluid production

FEATURES

- Available for 23/8-in and 27/8-in [60.325-mm and 73.025-mm] insert pump applications
- Designed with 11/4-in and 11/2-in [31.75-mm and 38.1-mm] cages

The Don-Nan bottom discharge valve is a two-component part placed on the barrel assembly between the standing and traveling valves. The valve acts as an intermediary valve that displaces approximately 10% of pumped fluid to the annulus between the outside of the pump and the tubing wall. This action moves fresh fluid past the exterior of the pump at the bottom end, keeping particulate matter from settling and sticking the pump as well as reducing adverse effects from corrosive fluid on the outside of the pump.



Bottom Discharge Valve



BUILT TO LAST

Made to Perform

Headquarters

811 Willow Oak Dr,
Missouri City, TX 77489
(281) 495-1100

Midland Campus

3427 E Hwy 158,
Midland, TX 79706
(432) 967-5575

LUFKIN Don-Nan is an API 11AX certified manufacturer for 25 continuous years and counting.

Ref: 09042022

lufkin.com/donnan