

Top Seal

Seal to prevent stuck pump scenario caused by solids accumulation

APPLICATIONS

- Wells with moderate to high particulate levels
- Intermittent pumping wells

BENEFITS

- Prevents stuck pump scenarios
- Eliminates particulate collection near the hold-down

FEATURES

- 1 1/4-in to 2-in [31.75-mm to 50.8-mm] insert pump sizes
- Replaceable rubber element
- Simple setting procedure

The Don-Nan top seal is a mechanical addition to any bottom hold-down insert pump, and it prevents a stuck pump scenario caused by solids accumulation around the hold-down. Once the pump has been placed in its seating location, the weight of the sucker rods on the pump pushes the rubber element outward until contact with the tubing wall is made. When retrieval of the pump is needed, pulling up on the rodstring will disengage the setting. Should the rubber element become damaged in operation, it may be replaced without replacing the entire assembly.



Top Seal

BUILT TO LAST

Made to Perform

Headquarters

811 Willow Oak Dr,
Missouri City, TX 77489
(281) 495-1100

Midland Campus

3427 E Hwy 158,
Midland, TX 79706
(432) 967-5575

LUFKIN Don-Nan is an API 11AX certified manufacturer for 25 continuous years and counting.

Ref: 09042022

lufkin.com/donnan